

# SAFETY DATA SHEET

# SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

Product ID:	ACBS-68002 / 68005 / 68030				
Product Name:	ArmorClay WB Mastic Adhesive				
Revision Date:	Apr 11, 2016	Date Printed:	Nov 11, 2016		
Version:	1.0	Supersedes Date:	N.A.		
Manufacturer's Name:	Mar-flex Waterproofing & Building Products				
Address:	500 Business Parkway Carlisle, OH, US,	500 Business Parkway Carlisle, OH, US, 45005			
Emergency Phone:	Chem-Trec: 1-800-424-9300				
Information Phone Numbe	:513-422-7285				
Fax:	513-422-7282				
Desides (/Desides and stated at the					

Product/Recommended Uses:

# SECTION 2) HAZARDS IDENTIFICATION

# Classification of the substance or mixture:

Not a hazardous substance or mixture according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

# Hazards Not Otherwise Classified (HNOC):

None.

## Additional hazard information:

May cause mild eye and skin irritation. Inhalation can cause mild irritation to the nose, throat and lungs.

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

# **SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS**

CAS	Chemical Name	% By Weight		
0009003-49-0	2-Propenoic acid, butyl ester, homopolymer	18% - 42%		
0001302-78-9	BENTONITE	13% - 17%		
0009003-07-0	POLYPROPYLENE	Trace		
Specific chemical identity and/or event percentage (concentration) of the composition has been withheld to protect confidentiality				

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

# **SECTION 4) FIRST-AID MEASURES**

### Inhalation:

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If unwell, or exposed and concerned : Get medical advice/attention.

## Eye Contact:

If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

## Skin Contact:

Rinse/wash with lukewarm, gently flowing water and mild soap for 5 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention immediately.

# Ingestion:

Rinse mouth. Give two glasses of water. If you feel unwell or if concerned : Get medical advice/attention. Note: Never give anything by mouth to an unconscious person.

## Most Important Symptoms and Effects, Both Acute and Delayed:

Exposure via inhalation can cause headache and nausea.

#### Indication of Any Immediate Medical Attention and Special Treatment Needed:

No data available.

## SECTION 5) FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media:

Dry chemical, foam, carbon dioxide. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Sand or earth may be used for small fires only.

#### Unsuitable Extinguishing Media:

No data available.

#### Specific Hazards in Case of Fire:

No data available.

#### **Fire-fighting Procedures:**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

#### **Special Protective Actions:**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## SECTION 6) ACCIDENTAL RELEASE MEASURES

#### **Emergency Procedure:**

ELIMINATE all ignition sources (no smokes, flares, sparks or flames in immediate area).

Isolate hazard area and keep unnecessary people away. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Do not touch or walk through spilled material.

If spilled material is cleaned up using a regulated solvent, the resulting mixture may be regulated.

#### **Recommended Equipment:**

If specialized clothing is needed, please refer to Section 8 for suitable and unsuitable materials.

#### Personal Precautions:

Avoid contact with skin or eye.

#### **Environmental Precautions:**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

#### Methods and Materials for Containment and Cleaning up:

Contain and collect spilled material with an inert absorbent and place in a container for disposal.

## SECTION 7) HANDLING AND STORAGE

#### General:

Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas.

Material is slippery when wet.

#### **Ventilation Requirements:**

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

### Storage Room Requirements:

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.

# SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Eye protection:

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

#### Skin Protection:

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory Protection:**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

## Appropriate Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA STEL (ppm)	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
No applicable chemical	-	-	-	-	-	-	-	-	-	-	-	-

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH TLV Basis	ACGIH Carcinogen	ACGIH Notations
No applicable chemical	-	-	-	-	-	-	-

# SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Ph	ysical and Chemical Properties					
	Density	9.18 lb/gal				
	% Solids By Weight	N/A				
	Density VOC	0.00 lb/gal				
	% VOC	0.00%				
	Specific Gravity	1.10				
	Appearance	White/grey paste				
	Odor Threshold	N/A				
	Odor Description	Acrylic or ammonia odor				
	рН	N/A				
	Water Solubility	Gels				
	Flammability	N/A				
	Flash Point Symbol	N/A				
	Flash Point	N/A				
	Viscosity	N/A				
	Lower Explosion Level	N/A				
	Upper Explosion Level	N/A				

Vapor Pressure	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N.A.
Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

# SECTION 10) STABILITY AND REACTIVITY

## Stability:

The product is stable under normal storage conditions.

## Conditions to Avoid:

Avoid heat, flame and contact with incompatible materials.

## Hazardous Reactions/Polymerization:

No data available.

# Incompatible Materials:

No data available.

## Hazardous Decomposition Products:

No data available.

## SECTION 11) TOXICOLOGICAL INFORMATION

## Likely Route of Exposure:

Eye or skin contact, inhalation

#### Skin Corrosion/Irritation:

May cause skin irritation.

## Serious Eye Damage/Irritation:

May cause eye irritation.

## **Respiratory/Skin Sensitization:**

No data available

## Germ Cell Mutagenicity:

No data available

## Carcinogenicity:

No data available

## **Reproductive Toxicity:**

No data available

## Specific Target Organ Toxicity - Single Exposure:

No data available

# Specific Target Organ Toxicity - Repeated Exposure:

# No data available

# Aspiration Hazard:

No data available

## Acute Toxicity:

May cause irritation to the mouth, throat and stomach.

## **SECTION 12) ECOLOGICAL INFORMATION**

## Toxicity:

No data available

#### Persistence and Degradability:

No data available.

## **Bio-accumulative Potential:**

No data available.

#### Other Adverse Effects:

No data available.

## SECTION 13) DISPOSAL CONSIDERATIONS

#### Waste Disposal:

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

## SECTION 14) TRANSPORT INFORMATION

#### **U.S. DOT Information:**

UN/NA #: Not regulated Proper Shipping Name: Not applicable Hazard Class: Not applicable Packing Group: Not applicable

## **IMDG** Information:

UN/NA #: Not regulated Proper Shipping Name: Not applicable Hazard Class: Not applicable Packing Group: Not applicable Marine Pollutant: No data available

## **IATA Information:**


UN/NA #: Not regulated Proper Shipping Name: Not applicable Hazard Class: Not applicable Packing Group: Not applicable

## **SECTION 15) REGULATORY INFORMATION**

CAS	Chemical Name	% By Weight	Regulation List
0009003-49-0	2-Propenoic acid, butyl ester, homopolymer	18% - 42%	SARA312,TSCA
0001302-78-9	BENTONITE		SARA312,TSCA,TSCA_UVCB - CHEMICAL SUBSTANCES OF UNKNOWN OR VARIABLE COMPOSITION, COMPLEX REACTION PRODUCTS AND BIOLOGICAL MATERIALS
0009003-07-0	POLYPROPYLENE	Trace	SARA312,IARCCarcinogen,TSCA

#### Glossary:

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDGCanadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- ESE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA-National Fire Protection Association; OEL- Occupational Exposure Limits; SOBA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.



## Version 1.0:

Revision Date: Apr 11, 2016 First Edition.

## DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.