



PRODUCT

Exterior Below-Grade Commercial Bentonite Waterproofing System
ArmorClay Termination Bar

Description

ArmorClay Termination Bar is a high strength vinyl/plastic strip designed for attaching and sealing ArmorClay membranes and drainage layers at their termination points. Term bar is 1" wide has pre-drilled holes and edging for caulking and sealing.

Installation

Surface should be clean, dry and free of contaminates. Install ArmorClay Termination bar at the top edge of material that it is to be supported. Fasten into substrate using pre-drilled holes with appropriate mechanical or power actuated fasteners. Apply a bead of silicone caulk to top of termination bar after application is complete. For specific installation guidelines, please contact your Mar-flex Representative or call Mar-flex at 800-498-1411.

Packaging

Cartons contain 50-6'6" strips per box.

Storage

Protect from moisture. Store in original shipping container on skid or pallet, cover with polyethylene or tarp.

Availability

Available worldwide through Mar-flex distributors. Please contact us, your Mar-flex Representative, or our website at <u>www.mar-flex.com</u> for details.

Limitations

Products as described herein are for industrial use only. The application procedures should be performed by workmen who are skilled in the application of material described herein in accordance with manufacturer specifications. Installation temperature is between -40° F to 150° F (-40° C to 65.5° C).

Limited Warranty

Mar-flex warrants its products will be delivered free of defects in materials and workmanship. Mar-flex will replace the material or refund the purchase price. Marflex makes no other warranty, including an implied warranty of merchantability or fitness for a particular purpose. Mar-flex shall not be liable for any other loss or damage. Contact Mar-flex to discuss specific details for extended warranty periods.

HEALTH AND SAFETY INFORMATION IS GIVEN IN THE SAFETY DATA SHEET (SDS) AND THE PRODUCT DATA SHEET AVAILABLE FOR THIS PRODUCT. THESE SHOULD BE READ AND UNDERSTOOD BEFORE USING THIS PRODUCT.