

# SAFETY DATA SHEET

# SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

Product ID: CWPR-12205
Product Name: ArmorPrimer 1200

**Revision Date:** Mar 25, 2015 **Date Printed:** Nov 11, 2016

Version: 1.0 Supersedes Date: N.A.

Manufacturer's Name: Mar-flex Waterproofing & Building Products

Address: 500 Business Parkway Carlisle, OH, US, 45005

Emergency Phone: Chem-Trec: 1-800-424-9300

Information Phone Number: 513-422-7285

Fax: 513-422-7282

Product/Recommended Uses:

# **SECTION 2) HAZARDS IDENTIFICATION**

### Classification:

Skin Irritation - Category 3 Eye Irritation - Category 2B Carcinogenicity - Category 2

# Pictograms:



# Signal Word:

Warning

# **Hazardous Statements - Health:**

Causes mild skin irritation

Causes eye irritation

Suspected of causing cancer.

# **Precautionary Statements - General:**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

# **Precautionary Statements - Prevention:**

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

# **Precautionary Statements - Response:**

If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

### **Precautionary Statements - Storage:**

Store locked up.

# **Precautionary Statements - Disposal:**

Dispose of contents/container to disposal recycling center.

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

### Hazards Not Otherwise Classified (HNOC):

None.

### Acute toxicity of 50% of the mixture is unknown

### **SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS**

 CAS
 Chemical Name
 % By Weight

 Proprietary
 Acrylic Polymer
 30% - 70%

 0000057-55-6
 PROPYLENE GLYCOL
 9% - 12%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

# **SECTION 4) FIRST-AID MEASURES**

### Inhalation:

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If breathing is difficult, administer oxygen.

### **Eye Contact:**

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

#### **Skin Contact:**

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water and mild soap for 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use.

### Ingestion:

Rinse mouth. If you feel unwell/ If concerned: Get medical advice/attention. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

### Most Important Symptoms and Effects, Both Acute and Delayed:

Possible cancer hazard.

# Indication of Any Immediate Medical Attention and Special Treatment Needed:

No data available.

# **SECTION 5) FIRE-FIGHTING MEASURES**

### Suitable Extinguishing Media:

Dry chemical, foam, carbon dioxide. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Sand or earth may be used for small fires only.

### **Unsuitable Extinguishing Media:**

Do not use direct water stream. Since this may cause fire to spread.

### Specific Hazards in Case of Fire:

No data available.

# Fire-fighting Procedures:

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Material may foam if heated above 212 F.

#### **Special Protective Actions:**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

# **SECTION 6) ACCIDENTAL RELEASE MEASURES**

#### **Emergency Procedure:**

ELIMINATE all ignition sources (no smokes, flares, sparks or flames in immediate area).

Isolate hazard area and keep unnecessary people away. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Do not touch or walk through spilled material.

If spilled material is cleaned up using a regulated solvent, the resulting mixture may be regulated.

### **Recommended Equipment:**

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

### **Personal Precautions:**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### **Environmental Precautions:**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

# Methods and Materials for Containment and Cleaning up:

Contain and collect spilled materials with non-combustible, absorbent material and place in a container for disposal according to local regulations. Dispose via a licensed waster disposal contractor. Contaminated absorbent material may pose the same physical hazards as the product.

### **SECTION 7) HANDLING AND STORAGE**

### General:

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

### **Ventilation Requirements:**

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

### **Storage Room Requirements:**

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container can retain residue and may be dangerous.

Protect from freezing

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Take measures to prevent the build up of electrostatic charge.

Ground and bond containers and receiving equipment. Avoid static electricity by grounding.

Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

# SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Eye protection:

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

### **Skin Protection:**

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory Protection:**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

### **Appropriate Engineering Controls:**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value

Chemical Name	OSHA STEL (ppm)	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
No applicable chemical	-	-	-	-	-	-	-	-	-	-	-	-

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH TLV Basis	ACGIH Carcinogen	ACGIH Notations	
No applicable chemical	-	-	-	-	-	-	-	

# **SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES**

#### **Physical and Chemical Properties**

Density 8.76 lb/gal
% Solids By Weight N/A
Density VOC 0.88 lb/gal
% VOC 10.00%
Specific Gravity 1.05

Appearance Blue Liquid
Odor Threshold N/A

Odor Description Slight Ammonia

pH N/A
Water Solubility Soluble
Flammability N/A
Flash Point Symbol N/A

Flash Point 109 C (PMCC) for Aqueous Solution of Propylene Glycol

Viscosity N/A
Lower Explosion Level N/A
Upper Explosion Level N/A

Vapor Pressure 23.7 mmHg
Vapor Density > 1 (Air=1)
Freezing Point N/A

Melting Point N/A
Low Boiling Point 212 °F
High Boiling Point N/A
Auto Ignition Temp N.A.
Decomposition Pt N/A

Evaporation Rate < 1 (Butyl Acetate = 1)

# **SECTION 10) STABILITY AND REACTIVITY**

### Stability:

The product is stable under normal storage conditions.

### **Conditions to Avoid:**

No data available.

# **Hazardous Reactions/Polymerization:**

No data available.

# **Incompatible Materials:**

Strong oxidizing agents.

### **Hazardous Decomposition Products:**

No data available.

# **SECTION 11) TOXICOLOGICAL INFORMATION**

### Likely Route of Exposure:

Inhalation, ingestion, skin absorption, eye contact.

### Skin Corrosion/Irritation:

Causes mild skin irritation

# Serious Eye Damage/Irritation:

Causes eye irritation

# Respiratory/Skin Sensitization:

No data available

# **Germ Cell Mutagenicity:**

No data available

### Carcinogenicity:

Suspected of causing cancer.

# **Reproductive Toxicity:**

No data available

# **Specific Target Organ Toxicity - Single Exposure:**

No data available

# **Specific Target Organ Toxicity - Repeated Exposure:**

No data available

# **Aspiration Hazard:**

No data available

# **Acute Toxicity:**

No data available.

# **SECTION 12) ECOLOGICAL INFORMATION**

**Toxicity:** 

No data available

# Persistence and Degradability:

No data available.

# **Bio-accumulative Potential:**

No data available.

### Mobility in Soil:

No data available.

#### Other Adverse Effects:

No data available.

# **SECTION 13) DISPOSAL CONSIDERATIONS**

### Waste Disposal:

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

# **SECTION 14) TRANSPORT INFORMATION**

### **U.S. DOT Information:**

UN/NA #: Not regulated Proper Shipping Name: Not applicable Hazard Class: Not applicable Packing Group: Not applicable

#### IMDG Information:

UN/NA #: Not regulated Proper Shipping Name: Not applicable Hazard Class: Not applicable Packing Group: Not applicable Marine Pollutant: No data available

#### **IATA Information:**

UN/NA #: Not regulated Proper Shipping Name: Not applicable Hazard Class: Not applicable Packing Group: Not applicable

# **SECTION 15) REGULATORY INFORMATION**

CAS	Chemical Name	% By Weight	Regulation List
0000057-55-6	PROPYLENE GLYCOL	9% - 12%	SARA312,VOC,TSCA

# **SECTION 16) OTHER INFORMATION**

### Glossary:

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDGCanadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- ESE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA-National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

# **HMIS**



(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

#### Version 1.0:

Revision Date: Mar 25, 2015

First Edition.

# **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.