

SAFETY DATA SHEET



Issue Date: Aug 01, 2018

Revision Date: New

Version: V01.2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Mar-flex Armor Masonry Sealer

Other Means of Identification

SDS #: CWSS-005

Recommended Use: Chemical Floor Hardener for Concrete

Restrictions on Use: No Data

Supplier of the Safety Data Sheet including Address:

Mar-flex Waterproofing Products
500 Business Parkway
Carlisle, OH 45005 USA

Telephone Numbers

Company Phone Number

Phone: 800-498-1411, 513-422-7285

Fax: 513-422-7282

Emergency Telephone : ChemTrec 800-424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Causes serious eye damage, causes severe skin burns and eye damage

GHS Classification:

Eye damage/irritation – Category 1

Skin Corrosion/Irritation – Category 1

Label Elements, including precautionary statements

Pictograms:



Signal Word: Danger

Hazard Statements:

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage.

Precautionary Statement(s)

Prevention:

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash hands and skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately Call a POISON CENTER/doctor.
- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P310 Immediately Call a POISON CENTER/doctor.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with plenty of soap and water or shower.
- P310 Immediately Call a POISON CENTER/doctor.
- P363 Wash contaminated clothing before reuse.
- P304+P340+P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately Call a POISON CENTER/doctor.

Storage: P405 Store Locked Up

Disposal: P501 Dispose of contents/container in accordance with local/regional/national regulations.

Hazards Not Otherwise Classified: Spilled material is slippery.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component

| | | |
|--------------------------------|--------------------|--------|
| Water | CAS No. 7732-18-5 | 80-90% |
| Potassium Methylsilanetriolate | CAS No. 31795-24-1 | 10-20% |

Ingredients not listed on this safety data sheet are considered to be non-hazardous according to OSHA 1910.1200 or are not present above their cutoff levels. Where a range is displayed, the exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

General Advice: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

Inhalation: Mist may cause respiratory irritation. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes (A minimum of 15 minutes is recommended). Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Ingestion: IF SWALLOWED: Do NOT induce vomiting. Rinse mouth with water. Never give anything by mouth to an unconscious person. Call a POISON CENTER or doctor if you feel unwell.

Skin Contact: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin irritation occurs: Get medical advice or attention.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray, alcohol-resistant foam, dry chemical, or carbon dioxide

Specific Hazards Arising from the Chemical

Not Applicable. Product is an aqueous non-combustible solution.

Hazardous Combustion Products

Carbon Oxides, Metal oxides, Silicon dioxide, Formaldehyde

Protective Equipment and Precautions for Firefighters

Wear self-contained breathing apparatus and full protective gear for firefighting.

Further Information

Compatible with all standard fire-fighting techniques

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment including protective clothing, eye and face protection. Spillage may be slippery.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains, soil or vegetation.

Methods and Material for Containment and Cleaning Up

Contain spillage with sand, earth or a suitable adsorbent and transfer to a container for disposal according to local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes. Use with adequate ventilation. Do not breathe mist.

Conditions for Safe Storage, Including any Incompatibilities

Keep at a temperature not exceeding 38 Degrees C (100 Degrees F). Do not allow material to freeze. Keep container tightly closed in a dry and well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not store with acids.

Unsuitable Containers: Aluminum

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component Exposure Limits

No occupational exposure limit has been assigned to Silicic acid, Sodium Salt. An exposure limit of 2 mg/m³ (15 min. TWA) is recommended by analogy with sodium hydroxide (UK EH40).

Appropriate Engineering Controls

Local Ventilation: Recommended

General Ventilation: Recommended

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: Use proper protection – Safety Glasses as a minimum

Skin and Body Protection: Wash at mealtime and end of shift. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc.). Use chemical protective gloves as a minimum and wash skin promptly upon any skin contact.

Respiratory Protection: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH or MSHA approved respirators.

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice. Wash hands before & after breaks and work day.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State: Liquid

Appearance: Clear

Color: Colourless

Odor: Odorless

Odor threshold: No Data

| <u>Property</u> | <u>Value</u> | <u>Remarks – Method</u> |
|-------------------------------------|----------------------|-------------------------|
| Vapor Pressure | Not Available | |
| Vapor Density | Not Available | |
| Relative Density | Not Available | |
| pH: | 10 | |
| Melting/Freezing Point | Not Available | |
| Solubility | Soluble in water | |
| Evaporation Rate | Not Available | |
| Flash Point | Not Relevant | |
| Flammability Limits | Not Relevant | |
| Flammability (Solid, gas) | Not Relevant | |
| Auto Ignition Temperature | Not Relevant | |
| Initial Boiling Point/Boiling Range | 100 Degrees C | |
| Decomposition Temperature | Not Available | |
| Viscosity | Not Available | |
| Specific Gravity | 1.15 at 25 Degrees C | 9.6 lbs./gallon |

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Possibility of Hazardous Reactions: When arc welding vessels containing aqueous solutions of this material, take care to control any explosion risk from hydrogen evolved by electrolysis. Aqueous solutions will react with aluminum, zinc, tin and their alloys evolving hydrogen gas which can form an explosive mixture with air. Material can react violently if in contact with acids. Material can react with sugar residues to form carbon monoxide.

Conditions to Avoid: See note above.

Incompatible Materials: See note above.

Hazardous Decomposition Products: Carbon Oxides, Metal oxides, Silicon dioxide, Formaldehyde

11. TOXICOLOGICAL INFORMATION

Potential Health Effects – Acute Toxicity

| | |
|-------------------|---|
| Ingestion | All symptoms of acute toxicity are due to high alkalinity. Material will cause irritation. Oral LD50 (rat) 3400 mg/kg bw. |
| Inhalation | Mist is an irritant to the respiratory tract. All symptoms of acute toxicity are due to high alkalinity. Inhalation LC50 (rat) >2.06 g/m ³ . |
| Skin | Causes severe skin burns and eye damage. |
| Eyes | Causes serious eye damage. |

Information on Physical, Chemical and Toxicological Effects:

See Acute Toxicity above

Delayed - Chronic Effects from Long-Term Exposure

None Known

Carcinogenicity: IARC, ACGIH, NTP, OSHA

None Known

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Fish (Brachydanio rerio) LC50 (96 hrs.) 1108 mg/l
Aquatic invertebrates: (Daphnia magna) EC50 (48 hrs.) 1700 mg/l

Persistence and Degradability: Inorganic. Soluble silicates, upon dilution, rapidly depolymerize into molecular species indistinguishable from natural dissolved silica.

Bioaccumulation: Inorganic. The substance has no potential for bioaccumulation.

Mobility: Not Applicable

Other Adverse Effects: The alkalinity of this material will have a local effect on ecosystems sensitive to changes in pH.

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes: This material is classified as hazardous waste under EC Directive 2008/98/EC and England and Wales Regulations SI 2005 No. 894. Offer surplus and non-recyclable solutions to a licensed disposal company. Disposal should be in accordance with local, state or national regulation.

Contaminated Packaging: Dispose of as unused product.

14. TRANSPORT INFORMATION

D.O.T.:

Not classified as a Dangerous Good

I.A.T.A.:

Not classified as a Dangerous Good

I.M.D.G.:

Not classified as a Dangerous Good

Marine Pollutant: No

15. REGULATORY INFORMATION

International Inventories

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

US Federal Regulations

SARA 302: None

SARA 311/312 Hazard Categories: Acute: Yes

SARA 313 Hazard Categories: None

CWA (Clean Water Act): None

Supplemental State Compliance Information:

California:

This product does not contain any amounts of a chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

New Jersey Right To Know:

| CAS Number | Component Name |
|------------|--------------------------------|
| 31795-24-1 | Potassium Methylsilanetriolate |

Pennsylvania Right To Know:

| CAS Number | Component Name |
|------------|--------------------------------|
| 31795-24-1 | Potassium Methylsilanetriolate |

U.S. EPA Label Information: No Data

16. OTHER INFORMATION

HMIS Classification:

| | |
|-------------------|---|
| Health hazard: | 2 |
| Flammability: | 0 |
| Physical Hazards: | 0 |

NFPA Rating:

| | |
|--------------------|---|
| Health hazard: | 2 |
| Fire: | 0 |
| Reactivity Hazard: | 0 |

Issuance Date: August 02, 2018

Revision Date: August 02, 2018

Revision Note: New

Date of Previous Version: None

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet