



WATERPROOFING MEMBRANE

LITEFUSION



Economical water-based gray acrylic waterproofing

LiteFUSION is an economical water-based acrylic waterproofing membrane for use when hydrostatic pressure exists. It has the ability to bridge cracks that might later develop in a foundation, and can protect from the dangers of moisture, which cause mold and mildew. Mar-flex LiteFUSION is specifically designed for waterproofing precast, poured and masonry foundation walls. Mar-flex LiteFUSION is a spray-on membrane, so it dries as a seamless, monolithic coating.



Mar-flex LiteFUSION (Water-Based) RWW-01-5 5 Gallon Bucket Each or 36/Pallet



Mar-flex LiteFUSION (Water-Based) RWW-01-55 55 Gallon Drum Each or 4/Pallet



Flexible, seamless coating that seals out moisture

LiteFUSION Advantages

- Water-based; No odor
- Stops water leaks in non structural concrete cracks
- Can be applied to damp walls
- · Seamless, monolithic coating
- Gray to blend in with concrete
- Can be applied to top of foundation walls
- Surface cures within 24-48 hours

LiteFUSION Spec Sheet	
	Water-Based
TOTAL SOLIDS	50-55%
APPLICATION METHOD	spray, brush or roller
APPLICATION RANGE	50°-100°F
WEIGHT / GALLON	10 lbs.
COVERAGE RATE	50 ft.² gal

 $^{^*}$ complete specs at Mar-flex.com

Try the complete line of Mar-flex products.

Foundation Waterproofing | Waterproofing Membranes | Dampproofing Products | Concrete Repair

Concrete Anchor Epoxies | Drainage Boards | Egress Window Wells | Standard Window Wells

Sealers/Mastics | Control Joint Systems | Air Barrier Systems | Vortex Vents